



All of Xavee products are designed to fit in any standard enclosure.



From Low Lux to Night Vision, check with your distributor for the appropriate Lux Camera.



You will see the difference the Xavee brand brings you.

VISIBLELY BETTER



EFFIO Xavee-700-2-12WDR

- Color 1/3" SONY ICX673AK(with Low Lux) CCD, 700TVL
- WDR Wide Dynamic Resolution
- 0.0001Lux/F2.0
- =65dB (AGC OFF)
- Noise Reduction
- IR Bullet Camera
- Indoor/outdoor
- Low Illumination
- IR LED: 36PCS IR LED working distance: 30M
- Lens: Varifocal 2.8-12mm Lens
- 700TV Lines Low Illumination, Effio, WDR, OSD, NR

Effio

By
CCTV GADGETS



Model Name	Xavee-700-4-9WDR
Pick-Up Device	1/3" EFFIO Color 1/3" SONY ICX673AK CCD Lines Low Illumination
Number of Pixels	700TV Lines Low Illumination, Effio, WDR, OSD, NR PAL:976 (H)× 494(V) NTSC :976 (H) ×582 (V)
System of Signal	NTSC PAL (special orders only - call sales department)
Resolution	700TV Lines
Minimum Illumination	0.0001Lux/F2.0
IR LED	35 PCS
IR Series Distance	40 M
Lens	Varifocal 2.8-12mm
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0.001 Lux/F1.4 (LED ON)
IR Power On	CDS Auto Control

S/N Ratio	≈65dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10c ~ +50c RH95% Max
Storage Temperature	-20c ~ +60c RH95% Max
White Balance	Auto
Power Source	DC12V 600mA
Dimension	200(W) x171(H) x83(D)mm
Weight	1300g