



All of Xavee products are designed to fit in any standard enclosure.



From Low Lux to Night Vision, check with your distributor for the appropriate Lux Camera.



You will see the difference the Xavee brand brings you.

VISIBLY BETTER



XAVEE EFFIO 700-4-9WDR

- Color 1/3" SONY ICX673AK(with Low Lux) CCD, 700TVL ATR, OSD, DNR
- WDR Wide Dynamic Resolution
- 0.001Lux/F2.0
- =65dB (AGC OFF)
- Noise Reduction
- Water resistance: IP66 Cable built-in bracket
- Low Illumination
- 5X42PCS IR LED working distance: 40M
- Lens: Varifocal 4-9mm Lens
- 700TV Lines Low Illumination, Effio, WDR, OSD, NR

Effio
By
XAVEE



| Model Name | Xavee-VAVR700IRWDR |
|----------------------|--|
| Pick-Up Device | 1/3" EFFIO Color1/3"SONY ICX673AK CCD Lines Low Illumination |
| Number of Pixels | 700TV Lines Low Illumination, Effio, WDR, OSD, NR PAL:976 (H)× 494(V) NTSC :976 (H) ×582 (V) |
| System of Signal | NTSC PAL (special orders only - call sales department) |
| Resolution | 700TV Lines |
| Minimum Illumination | 0.001Lux/F2.0 |
| IR LED | 42 PCS |
| IR Series Distance | 40 M |
| Lens | Varifocal 4-9mm |
| Sync System | Internal |
| IR Status | Under 10 Lux By CDS |
| Usable Illumination | 0.001 Lux/F1.4 (LED ON) |
| IR Power On | CDS Auto Control |
| S/N Ratio | =65dB (AGC OFF) |
| Gamma Correction | 0.45 |

| | |
|-------------------------|--|
| Video Out | Composite Signal (1.0Vp-p, 75Ω) |
| Scanning System | PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec |
| Electronic Shutter Time | Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec |
| Operation Temperature | -10c ~ +50c RH95% Max |
| Storage Temperature | -20c ~ +60c RH95% Max |
| White Balance | Auto |
| Power Source | DC12V 400mA |
| Dimension | 207(W)x184(H)x83(D)mm |
| Weight | 3lb |