



All of Xavee products are designed to fit in any standard enclosure.



From Low Lux to Night Vision, check with your distributor for the appropriate Lux Camera.



You will see the difference the Xavee brand brings you.

VISIBLY BETTER



XAVEE EFFIO Xavee-700-6IR

- Color 1/3" SONY ICX673AK(with Low Lux) CCD, 700TVL ATR, OSD, DNR
- WDR Wide Dynamic Resolution
- 0.001Lux/F2.0
- =65dB (AGC OFF)
- Noise Reduction
- Water resistance: IP66 Cable built-in bracket
- Low Illumination
- IR LED: \varnothing 5X36PCS IR LED working distance:25M
- 3-Axis Bracket
- 700TV Lines Low Illumination, Effio, WDR, OSD, NR

Effio
By
XAVEE



Model Name	Xavee-VAVR700IRWDR
Pick-Up Device	1/3" EFFIO Color1/3"SONY ICX673AK CCD Lines Low Illumination
Number of Pixels	700TV Lines Low Illumination, Effio, WDR, OSD, NR PAL:976 (H)× 494(V) NTSC :976 (H) ×582 (V)
System of Signal	NTSC PAL (special orders only - call sales department)
Resolution	700TV Lines
Minimum Illumination	0.001Lux/F2.0
IR LED	36 PCS
IR Series Distance	25 M
Lens	3.6mm
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0.001 Lux/F1.4 (LED ON)
IR Power On	CDS Auto Control
S/N Ratio	=65dB (AGC OFF)

Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10c ~ +50c RH95% Max
Storage Temperature	-20c ~ +60c RH95% Max
White Balance	Auto
Power Source	DC12V 500mA
Dimension	200(W)x82(H)x75(D)mm
Weight	880g