XAVEE
A WORLDWIDE LEADER IN OPTICS

All of Xavee products are designed to fit in any standard enclosure.

From Low Lux to Night Vision, check with your distributor for the appropriate Lux Camera.

You will see the difference the Xavee brand brings you.

VISIBLY BETTER



XAVEE-PT480

• Indoor PT Camera

- XAVEE-PT480 3.5" mini pan/tilt integrated dome camera
- SONY EXVIEW HAD CCD .
- Elegant design, small size,
- suitable for indoor application
- Support Pelco-P, Pelco-D, and WORLD protocol
- 64 pieces preset point. Imported high quality motor,
- board camera and lens; High precision with preset point, precision up to ±0.5°
- INCLUDES a ceiling Mount and a Wall Mount. Low operation noise, applied to quiet environment, such as the office, classroom, and stairs

INCLUDES: a ceiling Mount and a Wall Mount.

CCD	1/3" SONY IT EXVIEW HAD CCD
Max. Pixels	512(H) * 492 (W)
Resolution	480TVL
S/N	48dB
Lens	3.6mm,
Min. Illumination	0.5 Lux. (F1.4)
Iris	Auto
Video Output	1.0Vpp 75? , un-balance
Sync system	Internal
Contrast Emendation	0.45
Gain Control	29dB (Max.)
Shutter Control Way	Auto electronic shutter or non-screen flash way

Pan/Tilt:

Movement Scope	Pan: 355°turning
	Tilt: 0°?90°
Movement Speed	Pan: 0.5°/S ?45°/S
	Tilt: 0.5°/S?45°/S
Preset Point Quantity	64
Preset Point Precision	?0.05°
Cable Connection	RS485 anti-thunder trans-connector
Baud Rate	9600 bps, 2400bps
Construction	ABS plastic shell

Others:

Working Voltage	DC12V
Power	30W
Color	Opalescence
Size	110mm×110mm
Weight	450g
Installation Way	Wall Mount; Ceiling Mount;
Working Temperature	0C -50C Storage Temperature -20C-60C

* Pictures and specifications are subject to change without prior notice