



All of Xavee products are designed to fit in any standard enclosure.



From Low Lux to Night Vision, check with your distributor for the appropriate Lux Camera.



You will see the difference the Xavee brand brings you.

VISIBLY BETTER



Xavee-PTZ520AC-DN

- 520 TVL PTZ Camera (PELCO D Protocol)
- EVERYTHING INCLUDED 22x High Speed Optical Zoom (outdoor enclosure, heater/blower, Power Supply, wall mount, ceiling, Outdoor/indoor Ceiling/Wall Mount Speed Color Dome
- • Super Had CCD (Day & Night)
- • Low Noise Design
- • 360° Panning and 90° Tilt.
- • Multiprotocol, RS485
- • DC24V

PTZ with EVERYTHING INCLUDED (outdoor enclosure, heater/blower, wall mount, ceiling mount, etc)

Works with PELCO D protocol

Optical Technology Base: HIGH RESOLUTION COLOR 1/4" Sony SUPER HAD CCD

Picture Elements (Horz x Vert in mm): EIA/NTSC: 768H x 494V - CCIR/PAL: 752H x 582V

Resolution: 520TVL

Minimum Illumination: 0.05 Lux F1.6

S/N Ratio: >52 dB

Shutter Speed: 1/60

Zoom : 22X Optical 10X Digital

Focus : Auto / Manual

Iris : Auto / Manual

Pan Speed : 0~360° 15°/sec

Tilt Speed : 0~90° 15°/sec

Preset : 64 presets

Auto Cruise : At best 6 cruises

White Balance / Gain / AE Control : Auto / Manual

Video Output : 1V p-p, 75 ohms

Power Supply : INCLUDED AC24V +/- 10% 1.25 (w/ Fan/Heater)

Dimensions : 200-360mm

Weight : 4 Kg

Operating Temperature : -10°C to +50°C (w/ Housing)

SUPPORTED PROTOCOLS:

PELCO-D, PELCO-P/4800, PELCO-P/9600, SAMSUNG, B01, NEON, SANTACHI, PANASONIC, HUNDA600

LILIN, VICON, MOLYNX, KALATEL, VCL, ALEC, ULTRAK

* Pictures and specifications are subject to change without prior notice